

PRODUCT DATASHEET SPC.T CL 15 W 230 V E14

SPECIAL OVEN T | Incandescent lamps, tubular shape, for oven lighting



Areas of application

- Baking ovens
- Domestic baking ovens




TECHNICAL DATA

Electrical data

Nominal wattage	15 W
Construction wattage	15.00 W
Nominal voltage	230 V

Photometrical data

Luminous flux	85 lm
Luminous efficacy	5 lm/W
Color temperature	2700 K
Color rendering index Ra	> 99
Light color	927



Light technical data

Starting time	0 s
---------------	-----

Dimensions & Weight

Overall length	55.00 mm
Length with base excl. base pins/connection	57,00 mm
Light center length (LCL)	45,0 mm
Diameter	26,0 mm
Product weight	7.6 g

Lifespan

Lifespan	1000 h
•	

Additional product data

Base (standard designation) E14	
---------------------------------	--

Dimmable Yes Certificates & Standards Energy efficiency class Energy consumption 15.00 kWh/1000h Country-specific categorizations ILCOS IBT/C-15-230-E14-26 Order reference SPC.T26/57 CL 1		
Energy efficiency class Energy consumption Country-specific categorizations ILCOS IBT/C-15-230-E14-26 Order reference SPC.T26/57 CL 1 Energy labelling regulation data acc EU 2019/2015 Lighting technology used OTHER Non-directional or directional Mins or non-mains Light source cap-type (or other electric interface) Envelope No Color-tuneable light source No Color-tuneable light source No Anti-glare shield Correlated colour temperature type Claim of equivalent power Length Light to cordinate No Length S5.00 mm Height Width 26,0 mm Vidth Chromaticity coordinate y Other Conested (0.416 SPHERE_360	Mercury-free	Yes
Energy efficiency class G Energy consumption 15.00 kWh/1000h Country-specific categorizations ILCOS IBT/C-15-230-E14-26 Order reference SPC.T26/57 CL 1 Energy labelling regulation data acc EU 2019/2015 Lighting technology used OTHER Non-directional NDLS Mains or non-mains MLS Light source cap-type (or other electric interface) E14 Connected light source (LS) No Color-tuneable light source (LS) No Envelope No Envelope No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Claim of equivalent power No Length S5.00 mm Height Michael S6.00 mm Width 26,00 mm Width 26,00 mm Chromaticity coordinate y 0.416 Beam angle correspondence SPHERE_360	Capabilities	
Energy efficiency class Energy consumption 15.00 kWh/1000h Country-specific categorizations ILCOS IBT/C-15-230-E14-26 Order reference SPC.T26/57 CL 1 Energy labelling regulation data acc EU 2019/2015 Lighting technology used OTHER Non-directional or directional MoLS Mains or non-mains Light source cap-type (or other electric interface) Envelope No Color-tuneable light source Envelope No High luminance light source No Correlated colour temperature type Claim of equivalent power Length Height 26.0 mm Width Chromaticity coordinate x O.496 Chromaticity coordinate y Descriptions IBT/C-15-230-E14-26 DTHER DTHER AND OTHER OTHER NO OTHER SPHERE_360	Dimmable	Yes
Energy consumption 15.00 kWh/1000h Country-specific categorizations ILCOS IBT/C-15-230-E14-26 Order reference SPC.T26/57 CL 1 Energy labelling regulation data acc EU 2019/2015 Lighting technology used OTHER Non-directional or directional NDLS Mains or non-mains MLS Light source cap-type (or other electric interface) E14 Connected light source (CLS) No Color-tuneable light source No Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Length S5.00 mm Height 26,0 mm Width 26,0 mm Width 26,0 mm Chromaticity coordinate x Union SPHERE_360 Control Correspondence SPHERE_360	Certificates & Standards	
Country-specific categorizations ILCOS IBT/C-15-230-E14-26 Order reference SPC.T26/57 CL 1 Energy labelling regulation data acc EU 2019/2015 Lighting technology used OTHER Non-directional or directional NDLS Mains or non-mains MLS Light source cap-type (or other electric interface) E14 Connected light source (CLS) No Color-tuneable light source No Envelope No High luminance light source No Correlated colour temperature type SINGLE_VALUE Light of equivalent power No Length S5.00 mm Height 26,0 mm Width 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y 0.416 Beam angle correspondence SPHERE_360	Energy efficiency class	G
ILCOS Order reference SPC.T26/57 CL 1 Energy labelling regulation data acc EU 2019/2015 Lighting technology used OTHER Non-directional or directional Mins or non-mains MLS Light source cap-type (or other electric interface) Envelope No Color-tuneable light source No Envelope No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Claim of equivalent power Height Width 26,0 mm Width Chromaticity coordinate y Beam angle correspondence SPHERE_360	Energy consumption	15.00 kWh/1000h
Order reference SPC.T26/57 CL 1 Energy labelling regulation data acc EU 2019/2015 Lighting technology used OTHER Non-directional or directional NDLS Mains or non-mains MLS Light source cap-type (or other electric interface) E14 Connected light source (CLS) No Color-tuneable light source No Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Claim of equivalent power No Length S5.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x O.496 Chromaticity coordinate y O.416 Beam angle correspondence SPHERE_360	Country-specific categorizations	
Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Miss or non-mains MLS Light source cap-type (or other electric interface) E14 Connected light source (CLS) No Color-tuneable light source No Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Light of equivalent power No Height 26,0 mm Wridth Chromaticity coordinate x O.496 Chromaticity coordinate y DATHER NDLS STHER OTHER NDLS ANDLS STHER OTHER OTHER	ILCOS	IBT/C-15-230-E14-26
Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) E14 Connected light source (CLS) No Cotor-tuneable light source No Envelope No Anti-glare shield Correlated colour temperature type Claim of equivalent power Length Height Width 26,0 mm Width Chromaticity coordinate x Chromaticity coordinate y Beam angle correspondence NOTHER MLS LIBR MDLS L14 No No No No SINGLE_VALUE Claim of equivalent power No Chromaticity coordinate y O.416 SPHERE_360	Order reference	SPC.T26/57 CL 1
Non-directional or directional NDLS Mains or non-mains MLS Light source cap-type (or other electric interface) E14 Connected light source (CLS) No Color-tuneable light source No Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Claim of equivalent power No Length 55.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y 0.416 Beam angle correspondence SPHERE_360	Energy labelling regulation data acc EU 2019/2015	
Mains or non-mains Light source cap-type (or other electric interface) E14 Connected light source (CLS) No Color-tuneable light source No High luminance light source No Anti-glare shield Correlated colour temperature type SINGLE_VALUE Claim of equivalent power Length Height 26,0 mm Width Chromaticity coordinate x 0.496 Chromaticity coordinate y Beam angle correspondence F14 No No No Anti-glare shield No SINGLE_VALUE Claim of equivalent power No 46 Chromaticity coordinate y O.416 SPHERE_360	Lighting technology used	OTHER
Light source cap-type (or other electric interface) Connected light source (CLS) No Color-tuneable light source No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Claim of equivalent power No Height 26,0 mm Width Chromaticity coordinate x Chromaticity coordinate y Beam angle correspondence E14 No No 0 0 0 0 0 0 0 0 0 0 0 0 0	Non-directional or directional	NDLS
Connected light source (CLS) Color-tuneable light source Envelope No High luminance light source No Anti-glare shield Correlated colour temperature type Claim of equivalent power Length Height 55.00 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y Beam angle correspondence No No SHERE_360	Mains or non-mains	MLS
Color-tuneable light source No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Claim of equivalent power No Length S5.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y Beam angle correspondence SPHERE_360	Light source cap-type (or other electric interface)	E14
Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Claim of equivalent power No Length 55.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y 0.416 Beam angle correspondence SPHERE_360	Connected light source (CLS)	No
High luminance light source Anti-glare shield Correlated colour temperature type SINGLE_VALUE Claim of equivalent power No Length 55.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y Beam angle correspondence SPHERE_360	Color-tuneable light source	No
Anti-glare shield Correlated colour temperature type SINGLE_VALUE Claim of equivalent power No Length 55.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y Beam angle correspondence SPHERE_360	Envelope	No
Correlated colour temperature type Claim of equivalent power No Length 55.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y Beam angle correspondence SPHERE_360	High luminance light source	No
Claim of equivalent powerNoLength55.00 mmHeight26,0 mmWidth26,0 mmChromaticity coordinate x0.496Chromaticity coordinate y0.416Beam angle correspondenceSPHERE_360	Anti-glare shield	No
Length55.00 mmHeight26,0 mmWidth26,0 mmChromaticity coordinate x0.496Chromaticity coordinate y0.416Beam angle correspondenceSPHERE_360	Correlated colour temperature type	SINGLE_VALUE
Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y 0.416 Beam angle correspondence SPHERE_360	Claim of equivalent power	No
Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y 0.416 Beam angle correspondence SPHERE_360	Length	55.00 mm
Chromaticity coordinate x Chromaticity coordinate y 0.496 0.416 Beam angle correspondence SPHERE_360	Height	26,0 mm
Chromaticity coordinate y 0.416 Beam angle correspondence SPHERE_360	Width	26,0 mm
Beam angle correspondence SPHERE_360	Chromaticity coordinate x	0.496
	Chromaticity coordinate y	0.416
EPREL ID 714461	Beam angle correspondence	SPHERE_360
	EPREL ID	714461

AC35396,AC35396

LOGISTICAL DATA

Model number

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300310282	Folding box 1	61 mm x 23 mm x 27 mm	16.00 g	0.04 dm³
4050300774558	Bundle 10	82 mm x 62 mm x 110 mm	123.00 g	0.56 dm³
4050300961729	Shipping box 100	275 mm x 139 mm x 138 mm	1430.00 g	5.28 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.